

Base coat, Spray Base coat

25.01.2016 Version No. 2

SAFETY DATA SHEET

1 Identification of chemical product and information on the manufacturer and/or supplier

Product Name: Base coat, Spray Base coat

Manufacturer / supplier:

ECOPOL LLC.

35, Suvorova str., Dzerzhinsk, Nizhny Novgorod region, 606010, Russia

Telephone: (8313) 230351; 230839; 230781; 230746

Tel./fax: (8313) 254103; 274016

1.2 Emergency phone:

In an emergency, contact the National Center for Emergency Care.

2 Hazard (hazards) identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**

H226:	Flammable liquid. Vapours form explosive mixtures with air	Highly-flammable liquid. Hazard category 3
H317:	May cause an allergic skin reaction	Skin sensitization. Hazard category 1
H332:	Harmful if inhaled.	Acute toxicity (inhal.), Hazard Category 4
H335:	May cause respiratory tract irritations	Specific target organ toxicity. Hazard category 3
H336:	May cause drowsiness or dizziness.	Specific target organ toxicity. Hazard category 3

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

This product is classified and labelled according to the Regulation on the classification, labelling and packaging of substances and mixtures (CLP).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Warning

· **Hazard-determining components of labelling:**

Xylene

n-butyl acetate

· **Hazard statements**

H226:	Flammable liquid. Vapours form explosive mixtures with air
H317:	May cause an allergic skin reaction
H332:	Harmful if inhaled.
H335:	May cause respiratory irritation
H336:	May cause drowsiness or dizziness.

· **Precautionary statements**

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking;
- P261: Avoid breathing dust/fumes/gas/mist/vapours/spray.
- P271: Use only outdoors or in a well-ventilated area.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P312: Get medical advice if you feel unwell.
- P273: Avoid release to the environment.
- P102: Store out of children's reach.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**














Base coat, Spray Base coat

25.01.2016 Version No. 2

- **PBT:** No information available.
- **vPvB:** No information available.

3 Composition (information on ingredients)

- **3.2 Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additives.
- **Contained hazardous substances:**

Chemical name	H-statements	Pictograms, signal word (codes)
Butyl acetate Concentration, % (by weight) 20 to 75 CAS No. 123-86-4 EINECS No. 204-658-1 Index Number 607-025-00-1 REACH No. 01-2119485493-29- XXXX	Flam. Liq. 3 STOT SE 3	H226  GHS02 H336  GHS07 Wng
Dimethylbenzene (xylene) Concentration, % (by weight) 4 to 20 CAS No. 1330-20-7 EINECS No. 215-535-7 Index Number 601-022-00-9 REACH No. 01-2119488216-32- XXXX	Flam. Liq. 3 Acute Tox. 4 * Skin Irrit. 2 Acute Tox. 4 *	H226  GHS02 H312  GHS07 H315 H332 Wng
1-methoxypropane-2-ol acetate (methoxypropyl acetate) Concentration, % (by weight) 0.5 to 8 CAS No. 108-65-6 EINECS No. 203-603-9 Index Number 607-195-00-7 REACH No. 01-2119475791-29-XXXX	Flam. Liq. 3	H226  GHS02
hydrocarbons, C9, aromatic Concentration, % (by weight) 0.5 to 6 CAS No. 64742-95-6 EINECS No. 918-668-5 Index Number 649-356-00-4 REACH No. 01-2119455851-35-XXXX	Flam. Liq. 3 Asp. Tox. 1 STOT SE 3 STOT SE 3 Aquatic Chronic 2	H226  GHS02 H304  GHS07 H335  GHS08 H336 H411  GHS09 Dgr
2-Propenoic acid, 2-methyl-, 2-(dimethylamino)ethyl ester, polymer with butyl 2-propenoate, comps. with polyethylene glycol hydrogen maleate C9-11-alkyl ethers Concentration, % (by weight) < 3 CAS No. 1259547-09-5 EINECS No. Index Number	Skin sens. 1	H317  GHS07 Wng
Butan-1-ol (butanol) Concentration, % (by weight) < 2 CAS No. 71-36-3 EINECS 200-751-6 Index Number 603-004-00-6 REACH No. 01-2119484630-38 - XXXX	Flam. Liq. 3 Acute Tox. 4 * Acute Toxicity - Oral Skin Irrit. 2 Eye Dam. 1 STOT SE 3 STOT SE 3	H226  GHS02 H302  GHS07 H315  GHS05 H318 H335 H336 Dgr

Base coat, Spray Base coat

25.01.2016 Version No. 2

4 First aid measures

· 4.1 Description of first aid measures

· General advice:

Immediately remove any clothing contaminated by this product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the emergency (accident).

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness bring patient into stable side position for transport.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek medical help.

· After eye contact:

Rinse opened eye for several minutes under running water; then consult doctor.

Remove contact lenses if any, continue rinsing.

· After swallowing:

Rinse mouth and drink plenty of water. DO NOT induce vomiting. Get medical attention.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment

5 Fire-fighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, extinguishing powder or water spray jet.

Fight larger fires with water spray jet or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents:

Full water jet

· 5.2 Special hazards arising from the substance or mixture

The following substances can be released in case of fire:

Carbon monoxide (CO) and carbon dioxide (CO₂)

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

· Additional information

Cool endangered containers with water spray jet.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing. Keep unprotected people away.

Provide for sufficient ventilation.

Keep away from ignition sources.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Avoid contact with eyes and skin.

· 6.2 Environmental precautions:

Do not allow to enter sewers / surface or ground water / holes and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

· 6.3 Methods and materials for containment and cleaning up:

Provide for sufficient ventilation.

Absorb with liquid-binding wet material (sand, diatomite, chemical binder based on calcium silicate, universal binders, sawdust).

Send for recovery or disposal in suitable containers.

Dispose contaminated material as waste according to guidelines.

Base coat, Spray Base coat

25.01.2016 Version No. 2

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage of chemicals.

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Ensure good interior ventilation, especially at floor level (fumes are heavier than air).

Limit the amount of stocks at the workplace.

Use only in well ventilated areas.

Avoid contact with eyes and skin.

Do not breathe smoke / spray.

Ensure the check of the total used area of the production premise.

· Information about fire and explosion protection:

Fumes can combine with air to form an explosive mixture.

Flammable gas and air mixtures may be formed in empty containers.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Take precautionary measures against static discharge.

Apply explosion-proof instruments / valves and sparkless tools.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Storage requirements to be met by storerooms and containers:

Store in a cool location.

Observe the rules for storage of flammable liquids.

Observe water protection rules.

· Information about storage in one common storage facility:

Observe the rules for storage of flammable liquids.

· Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

8 Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

CAS No. 123-86-4 n-butyl acetate

OEL (RF) short-term maximum: 200 mg/m³

shift-average: 50 mg/m³

CAS No. 1330-20-7 xylene (isomer mixture)

OEL (RF) short-term maximum: 150 mg/m³

shift-average: 50 mg/m³

CAS No. 108-65-6: 1-methoxypropane-2-ol acetate

OEL (RF) short-term maximum: 10 mg/m³

MAC (maximum allowable concentration, USA): 50 ppm; 275 mg/m³;

DNEL values

CAS No. 123-86-4: n-butyl acetate

Area of application: worker (Inhalation)

Potential effects on health: Long-term exposure - systemic effects: 48 mg/m³

Area of application: worker (Inhalation)

Potential effects on health: Short-term exposure - no information available

Area of application: worker (dermatitis)

Potential effects on health: Long-term exposure - systemic effects: 7 mg/kg bw/day

Area of application: worker (dermatitis)

Base coat, Spray Base coat

25.01.2016 Version No. 2

Potential effects on health: Short-term exposure: no information available

CAS No. 1330-20-7: xylene

Area of application: worker (Inhalation)

Potential effects on health: Long-term exposure - systemic effects: 77 mg/m³

Area of application: worker (Inhalation)

Potential effects on health: Short-term exposure, systemic and local effects: 289 mg/m³

Area of application: worker (dermatitis)

Potential effects on health: Long-term exposure - systemic effects: 180 mg/kg bw/day

Area of application: worker (dermatitis)

Potential effects on health: Short-term exposure, local effects: no information available

CAS No. 108-65-6: 1-methoxypropane-2-ol acetate

Area of application: worker (Inhalation)

Potential effects on health: Long-term exposure, systemic effects: 275 mg/m³

Potential effects on health: Short-term exposure - local effects: 550 mg/m³

Area of application: worker (dermatitis)

Potential effects on health: Long-term exposure - systemic effects: 796 mg/kg bw/day

Potential effects on health: Short-term exposure, local effects: not identified

CAS No. 64742-95-6 hydrocarbons, C9, aromatic

Area of application: worker (Inhalation)

Potential effects on health: Long-term exposure - systemic effects: 150 mg/m³

Area of application: worker (dermatitis)

Potential effects on health: Long-term exposure - systemic effects: 25 mg/kg bw/day

Area of application: worker (dermatitis)

Potential effects on health: Short-term exposure, local effects: no information available

PNEC values

CAS No. 123-86-4: n-butyl acetate

freshwater: 0.18 mg/l

marine water: 0.018 mg/l

soil: 0.09 mg/kg soil dw

CAS No. 1330-20-7: xylene

freshwater: 0.327 mg/l

marine water: 0.327 mg/l

soil: 2.31 mg/kg soil dw

CAS No. 108-65-6: 1-methoxypropane-2-ol acetate

freshwater: 0.635 mg/l

marine water: 0.064 mg/l

soil: 0.29 mg/kg soil dw

Additional information:

The lists valid during manufacture were used as basis.

8.2 Exposure controls / personal protection

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases/fumes/sprays.

Avoid contact with eyes and with skin.

Wash hands before breaks and at the end of work.

Do not put the product-soaked rags in trouser pockets.

Respiratory protection:

If workplaces are well-ventilated precautions are not required.

Hand protection:

Rubber gloves.

Eye protection: Tightly sealed safety glasses

Body protection:

Protective work clothing

Body protection must be chosen depending on the type of activity and possible exposure.

Environmental exposure controls

Do not allow to enter sewers / surface or ground water.

Base coat, Spray Base coat

25.01.2016 Version No. 2

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General information

Appearance	Liquid
Colour	Required
Odour	Of organic solvents
pH	Not specified
Boiling point	Not specified
Flash point (Closed cup)	Plus 29 ⁰ C (butyl acetate) Plus 24 ⁰ C (dimethylbenzene) Plus 45 ⁰ C (1-methoxypropane-2-ol acetate) Plus 51 ⁰ C (hydrocarbons, C9, aromatic)
Self-ignition temperature	Plus 370 ⁰ C (butyl acetate) Plus 494 ⁰ C (dimethylbenzene) Plus 315 ⁰ C (1-methoxypropane-2-ol acetate) Plus >400 ⁰ C (hydrocarbons, C9, aromatic)
Density, g/cm ³	1.0
Viscosity (relative, sec)	Not specified
Lower explosion limit, % by volume	2.2 (butyl acetate) 1.0 (dimethylbenzene) 1.5 (1-methoxypropane-2-ol acetate) 0.7 (hydrocarbons, C9, aromatic)
Upper explosion limit, % by volume	14.7 (butyl acetate) 6.0 (dimethylbenzene) 7.0 (1-methoxypropane-2-ol acetate) 7.0 (hydrocarbons, C9, aromatic)
Vapour density (Pa/at 20°C)	Not specified
Solids content, % by weight	20-50
Solubility in water	Insoluble

· 9.2 Other information No further relevant information available.

10 Stability and reactivity

10.1 Chemical stability

Stable under recommended storage and handling conditions.

10.2 Chemical reactivity

None under recommended storage and handling conditions.

10.3 Conditions to avoid

Direct sunlight, high temperatures, open flames, sparks.

Contact with strong oxidizing agents, peroxides, strong acids and bases.

10.4 Hazardous decomposition products

Thermal decomposition can release carbon monoxide and other toxic gases.

11 Toxicological information

· 11.1 Information on toxicological effects

· Acute toxicity:

· LD/LC50 (lethal dose/concentration) values relevant for classification:

CAS No. 123-86-4 n-butyl acetate

Oral (by mouth) LD50 14,130 mg/kg (rat)

Dermal (through the skin) LD50 > 17,600 mg/kg (rabbit)

CAS No. 1330-20-7 xylene (isomer mixture)

Oral (by mouth) LD50 3523 mg/kg (rat)

Base coat, Spray Base coat

25.01.2016 Version No. 2

Dermal (through the skin) LD50 12,126 mg/kg (rabbit) (by m-xylene)

Inhalation LC50/4 h 27,124 mg/m³ (rat)

CAS No. 108-65-6: 1-methoxypropane-2-ol acetate

Oral (by mouth) LD50 5465-7553 mg/kg (rat)

Dermal (through the skin) LD50 2000 mg/kg (rat)

CAS No. 64742-95-6 hydrocarbons, C9, aromatic

Oral (by mouth) LD50 3492 mg/kg (rat)

Dermal (through the skin) LD50 > 3160 mg/kg (rabbit)

• **Primary irritant effect:**

• **on the skin:** Prolonged or repeated contact may defat the skin and result in dermatitis.

• **on the eye:** Irritant effect.

• **Subacute to chronic toxicity:** not classified

• **Additional toxicological information:**

The product shows the following hazards according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

Danger of skin absorption.

• **Information on the following groups of potential effects:**

• **Sensitization** No sensitizing effects known.

• **Repeated dose toxicity** not determined

• **Carcinogenicity, mutagenicity and toxicity for reproduction**

According to present knowledge no CMR-effects known.

12 Ecological information

• **12.1 Toxicity**

CAS No. 123-86-4 n-butyl acetate

ErC50/72 h 648 mg/l (Scenedesmus subspicatus) growth inhibition in algae

EC50/48h 44 mg/l (Daphnia sp.) / for aquatic invertebrates

LC50/96 h 18 mg/l (Pimephales promelas) / for fish

CAS No. 1330-20-7 xylene (isomer mixture)

EbC50/73 h 2.2 mg/l (Selenastrum capricornutum)(by p-xylene) / for algae

EC50/48 h >3.4 mg/l (Ceriodaphnia dubia)(by m-xylene) / for aquatic invertebrates

LC50/96h 11.23 mg/l (Bryconamericus iheringii)(by m-xylene)/for fish

NOEC/56 days >1.3mg/l (Salmo gairdneri)/ for fish

CAS No. 108-65-6: 1-methoxypropane-2-ol acetate

EC50/72h > 1000 mg/l. (Selenastrum capricornutum) /for algae

EC50/48 h 373 mg/l (Daphnia magna) / for aquatic invertebrates

LC50/96h >100 mg/l (oryzias latipes) /for fish

CAS No. 64742-95-6 hydrocarbons, C9, aromatic

ErL50/72 h 7.9 mg/l (Selenastrum capricornutum) growth inhibition / for algae

EC50/48h 44 mg/l (Daphnia magna) / for aquatic invertebrates

LL50/96h 9.2 mg/L (Oncorhynchus mykiss) / for fish

• **12.2 Persistence and degradability**

No further relevant information available.

• **12.3 Bioaccumulative potential** No further relevant information available.

• **12.4 Mobility in soil** No further relevant information available.

• **Additional ecological information:**

• **General notes:**

The product contains volatile organic components. Do not allow product to reach ground, water, water course or sewage system and biological treatment plants.

• **12.5 Results of PBT and vPvB assessment**

• **PBT:** No information available.

Base coat, Spray Base coat

25.01.2016 Version No. 2

- **vPvB:** No information available.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations**13.1 Waste treatment methods**

· **Recommendation:**

Disposal must be made according to official regulations.

· European waste catalogue

Waste disposal key numbers have to be assigned depending on origin and processing.

· Uncleaned packaging:

· **Recommendation:**

Must not be disposed of together with household garbage. Contaminated packaging must be transported to the companies authorized to collect, recycle or dispose waste.

14 Transport information

	ADR/RID	IMDG	IATA
14.1 UN number	1263	1263	1263
14.2 UN shipping name		PAINT	
14.3 Transport classification	3	3	3
14.4 Packing Group	III	III	III
Environmental hazards:	No	No	No
14.5 · Marine pollutant:			
14.6 Special precautions for user			
	Do not transport together with materials of class 1; class 4.2; class 4.3; class 5.		
	Do not use open flame and no smoking		

15 Regulatory information**· 15.1 Safety norms, health and environmental regulations/legislation specific for the substance or mixture****· National regulations:****· Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road
RID:	Regulations Concerning the International Transport of Dangerous Goods by Rail
IMDG:	International Maritime Code for Dangerous Goods
IATA:	International Air Transport Association
GHS:	Globally Harmonised System of Classification and Labelling of Chemicals
EINECS:	European Inventory of Existing Commercial Chemical Substances
ELINCS:	European List of Notified Chemical Substances
CAS:	Chemical Abstracts Service (division of the American Chemical Society)
REACH:	Registration Evaluation and Authorisation of Chemicals
DNEL:	Derived No-Effect Level (REACH)
PNEC:	Predicted No-Effect Concentration (REACH)
NOEC:	No observed effect concentration
LC50:	Lethal concentration, 50 percent
LD50:	Lethal dose, 50 percent
Flam. Liq. 3	Flammable liquids, Hazard Category 3
STOT SE 3	Specific target organ toxicity, Hazard Category 3
Acute Tox. 4 *	Acute toxicity, Hazard Category 4
Skin Irrit. 2	Skin corrosion/irritation, Hazard Category 2

Base coat, Spray Base coat

25.01.2016 Version No. 2

<i>Asp. Tox. 1</i>	<i>Aspiration Hazard Category 1</i>
<i>Aquatic Chronic 2</i>	<i>Hazardous to the aquatic environment – chronic Category 2</i>
<i>Skin Sens. 1</i>	<i>Skin Sensitisation. Category 1</i>
<i>Eye Dam. 1.</i>	<i>Serious Eye Damage / Eye Irritation Category 1</i>
<i>GHS02</i>	<i>Hazard pictogram: flame</i>
<i>GHS05</i>	<i>Hazard pictogram: corrosion (also used to denote hazard to human health)</i>
<i>GHS07</i>	<i>Hazard pictogram: exclamation mark</i>
<i>GHS08</i>	<i>Hazard pictogram: health hazard</i>
<i>GHS09</i>	<i>Hazard pictogram: environment</i>
<i>Wng</i>	<i>Warning</i>
<i>Dgr</i>	<i>Danger</i>
<i>H226:</i>	<i>Flammable liquid. Vapours form explosive mixtures with air</i>
<i>H302:</i>	<i>Dangerous if swallowed</i>
<i>H304</i>	<i>May be fatal if swallowed and enters airways</i>
<i>H312:</i>	<i>Harmful in contact with skin</i>
<i>H315:</i>	<i>Causes skin irritation</i>
<i>H317:</i>	<i>May cause an allergic skin reaction</i>
<i>H318:</i>	<i>In contact with eyes, causes irreversible effects// Causes serious damage to eyes</i>
<i>H332:</i>	<i>Harmful if inhaled</i>
<i>H335:</i>	<i>May cause respiratory irritation</i>
<i>H336:</i>	<i>May cause drowsiness or dizziness.</i>
<i>H411:</i>	<i>Toxic to aquatic life with long lasting effects</i>